

Product Name :
Flame Photometer

Product Code :
NLAB-TESTINGLABM32002



Description :

Flame Photometer

Technical Specification :

Flame Photometer

- Simple & Easy to Operate.
- Narrow Band Interference Filters.
- Dual Channel Display.
- Na & K at Single Aspiration.

<td+ 2% upto 100 meq/l

Flame Photometer Unit
Na, K (Ca & Li optional)
Range: 200 meq/L to 2000 meq/L
K: 0-100 meq/L to 1000 meq/L

Na & K: 10 ppm
Ca: 10 ppm
K: 5 ppm
Li: 10 ppm
Display: 12.1" High Bright Display
Accuracy: 40 ppm
+ 5% above 40 ppm
Repeatability
Sensitivity
Photo diode
Narrow band interference glass filters
Blacklight, axial flow type
EPOXY oil free air
10 minutes
230V ± 10% AC 50 Hz
355 x 255 x 110 mm
Weight (Approx.)
Compressor Unit
Air Supply: mini compressor unit with pressure regulator
Controlled by precision regulator
230V ± 10% AC 50 Hz
375 x 182 x 140 mm
Weight (Approx.)
Accessories with Na & K Filters, Instruction Manual, Dustcover, Chimney, Air Tubing

Naugralabequipments

Website: www.naugralabequipments.com, **Email:** sales@naugralabequipments.com

Address: 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India. **Phone:** +91-9896600003