

Product Name :
Linear Heat Conduction

Product Code :
DM498



Description :

Linear Heat Conduction

Technical Specification :

Linear Heat Conduction

Heating section: cylinder of brass with diameter of 25 mm, provided with cartridge resistance of 60 W @ 24 Vdc, safety thermostat and with three K-type thermocouples

Cooling section: water-cooled cylinder of brass with diameter of 25 mm, provided with three thermocouples, pressure reducer & filter and with control valve

Intermediate section of brass: cylinder with diameter of 25 mm and length of 30 mm, provided with two housings for thermocouples placed at a distance of 15 mm

Intermediate section of stainless steel: cylinder with diameter of 25 mm and length of 30 mm, provided with two housings for thermocouples placed at a distance of 15 mm

Intermediate section of aluminum: cylinder with diameter of 25 mm and length of 30 mm, provided with two housings for thermocouples placed at a distance of 15 mm

Intermediate section of brass: cylinder of steel with diameter of 13 mm and length of 30 mm, provided with two housings for thermocouples placed at a distance of 15 mm

Two disks of insulating material (paper and PTFE) with thickness of 1 mm.

Website: www.naugralabequipments.com, **Email:** sales@naugralabequipments.com
Address: 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India. **Phone:** +91-9896600003

Naugralabequipments