

Product Name :
Microtome Fully Automatic Rotary

Product Code :
NLAB-LABORATORYEM28022



Description :

Microtome Fully Automatic Rotary

Technical Specification :

Compatible Embedding Material paraffin, plastic.

The cutting and trimming function can be finished by the control system.

The hand wheel can be locked at any position, so as to ensure the safety of the operation.

The large waste tray can be Exchanged arbitrarily.

Two kinds of the specimen clamp can be changed conveniently, and it has the alarm system.

Two model for section: Manual and automatic, the user can switch arbitrarily.

Four speed of section: 25 circle/minute, 35 circle/minute, 45 circle/minute, 55 circle/minute.

Switch arbitrarily between section and trimming.

Alarm system for horizontal and vertical stock limit, protection system for motor surcharge.

Technical Specifications of Microtome Fully Automatic Rotary :

Range of the thickness of slice: 0?100?m

Range of the thickness of trimming: 0?100?m

Setting thickness of slice ranges:

0?10?m increment 0,5?m

10?20?m increment 2?m

20?100?m increment 5?m

Horizontal specimen stroke: 26mm

Vertical specimen stroke: 60mm

The retraction of the specimen clamp: 20?m

Orientation of the specimen head: 360°

Minimum setting thickness of slice: 0,5?m

Maximum section of slice: 50×50mm

Slice precision: ±10%

Naugralabequipments

Website: www.naugralabequipments.com, **Email:** sales@naugralabequipments.com

Address: 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India. **Phone:** +91-9896600003