

Product Name :
Petroleum Products Kinematic Viscosity Tester

Product Code :
NLAB-EDUCATIONTVET39011



Description :

Petroleum Products Kinematic Viscosity Tester

Technical Specification :

Power supply: AC 220V $\pm$ 10%, 50Hz;

Heating power: 1700W;

Temperature range: Ambient temperature~100.0°C;

Temperature controlling accuracy: $\pm 0.01^{\circ}\text{C}$;

Bath cubage: 20 L;

Timing range: 0.0s~9999.9s;

Timing accuracy: Not more than $\pm 0.05\%$ in 60 min;

Sample quantity: 4 pieces at the same time;

Stirring motor: 6W, 1200RPM;

Operation environment:

Ambient temperature: -10°C~35°C;

Relative humidity: 85%;

Temperature sensor: Industrial platinum, PT100;

Total power consumption: Not more than 1800 W;

Capillary Viscometer: 7 pieces in a group; The inner diameters of them are 0.6, 0.8, 1.0, 1.2, 1.5, 2.0, 2.5mm respectively.

Naugralabequipments

Website: www.naugralabequipments.com, **Email:** sales@naugralabequipments.com

Address: 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India. **Phone:** +91-9896600003