

Product Name :
Pile Echo Tester concrete

Product Code :
NLAB -CONCRLAB120047



Description :

Pile Echo Tester concrete

Technical Specification :

Noise Voltage of The System (mV): ?2

Dynamic Range (dB): ?184

Amplifier Frequency Band (Hz): 1 – 10 k

A/D Resolution: 24 bit A/D

Sampling Time Intervals: 1 ?s – 6400 ?s

Max. Length of Sampling: ?4096

Amplitude Nonlinear Degree: ?10%

Error of Time Indication: ?1%

Gain Error: ?1 dB

Fixed Point Magnification: 1,2,5,10,20,50,100

Number Of Channels: 2

Phase Position Consistency of Two Channels: $\pm 3^\circ$ 0.05 ms

Inter-channel Interference: $\pm 3\%$ $\pm 0.2\text{dB}$

Triggering Mode: $\pm 1\%$

Acceleration Transducer Sensitivity (mV/g): ± 100 mV/g

Frequency Range of Acceleration Transducer: 0.5 – 9000 Hz

Continuous Operating Hours: > 5 hrs

Power Supply Mode: Rechargeable Lithium Battery Inside DC 9V

Display: 5.7 inch, TFT True Color LCD

Naugralabequipments

Website: www.naugralabequipments.com, **Email:** sales@naugralabequipments.com

Address: 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India. **Phone:** +91-9896600003