Phone: +91-9896600003

Email: sales@naugralabequipments.com

Product Name:

Vacuum Oven GMP Model

Product Code:

NLAB-SCIENTIFICEQ39006



Description:

Vacuum Oven GMP Model

Technical Specification:

APPLICATIONS OF VACUUM OVEN GMP

In Double Walled Vacuum Oven the thermal process occur in airtight chamber under desired level of vacuum and maintained temperature. It can help in the prevention of surface reactions (such as oxidation), decontaminating samples (removing lubricants for example) as well as for speeding up the out gassing process.

Double Walled Vacuum Oven is low cost options for Moisture Determination, Out Gassing Solids, Aging Tests, Plating, Chemical Resistance Studies, Drying of Paper, Rubber, and Textiles, Desiccating, Dry Sterilization, Out Gassing Liquids, Vacuum Storage, Electronic Process Control.

Vacuum Ovens are used for various experiments in, industries, R&D labs, Pharmaceutical, Food & Beverage Industries and Institutions- in the field of Medical, Agricultural and Industrial Research.

SALIENT FEATURES & CONSTRUCTION OF VACUUM OVEN GMP

Outer & Inner Chamber is made of STAINLESS STEEL.

Thermal loss is prevented by filling mineral wool (Insulation) in space between the outer body & Inner chamber.

Provided with Door Gasket for proper sealing.

Phone: +91-9896600003

Email: sales@naugralabequipments.com

Fitted with heavy hinges & door closing device.

See through transparent window of toughened glass is provided at the front.

Adjustable two air controlling valves are fitted for creation of vacuum in the chamber & release.

Heating elements are made of high quality Nichrome/Kanthal wire are embedded around the chamber.

Supplied with 1 or 2 removable shelves.

Temperature is controlled by electronic digital temperature indicator cum controller from 50°C to $130^{\circ}\text{C} \pm 2^{\circ}\text{C}$. fitted on the front panel for easy operations.

Temperature is displayed by Digital LED with SV and PV display at front of the oven.

Front Panel is provided with ON/OFF switch, temperature controller and indicators

Supplied with cord and plug.

Operating Voltage: 220 Volts AC (50 Hz).

Naugralabequipments

Website: www.naugralabequipments.com, Email: sales@naugralabequipments.com
Address: 6148/6, Guru Nanak Marg,Ambala Cantt,Haryana,India. Phone: +91-9896600003